

PCB Layout Diagram  
Top View

- NOTE:
1. ALL INSIDE BEND RADII TO BE A MIN. OF MATERIAL THICKNESS UNLESS OTHERWISE SPECIFIED.
  2. PART MUST BE FREE OF ALL BURRS AND SHARP EDGES.
  3. MAT'L: 0.254 TH'K FULL HARD PHOSPHOR BRONZE
  4. FINISH: NICKEL PLATE  
0.00254-0.00762 NICKEL, OVER  
0.00127-0.00254 COPPER
  5. INDICATES CRITICAL DIMENSION


Order code:

BS - S - SI - B - CR1632A  
① ② ③ ④ ⑤

- ① BS: Battery Contacts
- ② Apperance for the product  
M: SMT TYPE  
S: 180 TYPE  
R: 90 TYPE
- ③ Contact Plating  
SI: NICKEL PLATE  
SN: Tin  
G0: Gold flash  
G1: 3U" Gold  
G2: 5U" Gold  
G3: 10U" Gold  
G4: 15U" Gold  
G5: 30U" Gold
- ④ Packing method  
A: Tray packing  
B: PE bag packing  
R: Tape & reel packing
- ⑤ Product number  
CR1632A

Unless Otherwise specified tolerance  
X. ±0.35 X.XX: ±0.20  
X.X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm  
DRAW ZLA DATE 21/07/2022  
CHECK BobYang DATE 21/07/2022



**Atkconn**® ATKCONN ELECTRONICS CO., LTD  
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE:  
Battery Contacts FOR CR1632A DIP  
DRAWING NO: BS-S-SI-B-CR1632A  
PRODUCT NO: BS-S-SI-B-CR1632A

REV	DESCRIPTION	DATE
1		