


NOTES:
 1. MATERIAL:
 FINISH NICKEL PLATED
 2. COATING PARAMETERS:4um
 3. TEMPERATURE RANGE:-40° C - 270° C
 4. VOLTAGE PARAMETERS:270V

BS - S - SI - B - CR329
 ① ② ③ ④ ⑤

- ① BS: Battery Contacts
- ② Apperance for the product
 M:SMT TYPE
 S:180 TYPE
 R:90 TYPE
- ③ Contact Plating
 SI:Nickel Plate
 SN:Tin
 G0:Gold flash
 G1: 3U" Gold
 G2: 5U" Gold
 G3:10U" Gold
 G4:15U" Gold
 G5:30U" Gold
- ④ Packing method
 A: Tray packing
 B:BAG PACKING
 R: Tape & reel packing
- ⑤ Product number
 CR329

Unless Otherwise specified tolerance
 X. ± 0.35 X. XX: ± 0.20
 X. X: ± 0.25 X. XXX: ± 0.15

SCALE: As Shown UNIT: mm
 DRAW ZLA DATE 21/07/2022
 CHECK BobYang DATE 21/07/2022



Atkconn® ATKCONN ELECTRONICS CO., LTD
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: BATTERY CONTACTS FOR 329

DRAWING NO: BS-S-SI-B-CR329

PRODUCT NO: BS-S-SI-B-CR329

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		