

Overall flatness of bottom surface of shell.

All bending and forming shall be adjustable.


- NOTES:
1. MATERIAL: ANNEALED SPRING STEEL, T=0.25mm.
 2. PLATING:
80U" Min TIN PLATED OVERALL
50U" Min NICKEL PLATED UNDER OVERALL

Order code:
BS - M - SN - X - 5231

- ① BS: Battery Contacts
- ② Appearance for the product
M: SMT TYPE
S: 180 TYPE
R: 90 TYPE
- ③ Contact Plating
SI: NICKEL PLATE
SN: Tin
G0: Gold flash
G1: 3u" Gold
G2: 5u" Gold
G3: 10u" Gold
G4: 15u" Gold
G5: 30u" Gold
- ④ Packing method
A: Tray packing
R: Tape & reel packing
B: Bag packing
- ⑤ Product number
5231: 5231 STYLE

Unless Otherwise specified tolerance
X. ±0.35 X.XX: ±0.20
X.X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
DRAW: ZLA DATE: 21/07/2022
CHECK: BobYang DATE: 21/07/2022



Atkconn® ATKCONN ELECTRONICS CO., LTD
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: Cell Battery Contacts 5231

DRAWING NO: BS - M - SI - X - 5231
PRODUCT NO: BS - M - SI - X - 5231

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		