

Note:

1. Material:

- a. Housing: PBTVO+GF BK
- b. Contact: C5191
- c. Surface Plating: Sn 10u"

2. Electric:

- a. Contact Resistance: 30 Milliohms Max.
- b. Insulation Resistance: 1000 Mega Ohms Min.
- c. Dielectric Voltage: 500 V AC One Sec Level
- d. Operating Temperature: -55° To +105°

Order code:

BT — S — SN — R — CR1220C  
 ① ② ③ ④ ⑤

① BT: Coin Cell Holders

② Appearance for the product

- M: SMT TYPE
- S: 180 TYPE
- R: 90 TYPE

③ Contact Plating

- SN: Tin
- G0: Gold flash
- G1: 3U" Gold
- G2: 5U" Gold
- G3: 10U" Gold
- G4: 15U" Gold
- G5: 30U" Gold

④ Packing method


- A: Tray packing
- R: Tape & reel packing

⑤ Product number

CR1220C

Unless Otherwise specified tolerance  
 X. ±0.35 X.XX: ±0.20  
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm  
 DRAW ZLA DATE 21/07/2022  
 CHECK BobYang DATE 21/07/2022



**Atkconn**® ATKCONN ELECTRONICS CO., LTD  
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: Coin Cell Holders For CR1220

DRAWING NO: BT-S-SN-R-CR1220C

PRODUCT NO: BT-S-SN-R-CR1220C

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		