

PCB LAYOUT (TOP VIEW)

Note:

1. Material:

- a. Housing: PPS Colr: Nature, UL94V-0
- b. Contact: C5191
- c. Surface Plating: Au

2. Electric:

- a. Contact Resistance: 30 Milliohms Max.
- b. Insulation Resistance: 1000 Mega Ohms Min.
- c. Dielectric Voltage: 500 V AC One Sec Level
- d. Operating Temperature: -30° To +70°


Order Code:

△ BT - M - GO - R - CR1220A
 ① ② ③ ④ ⑤

- ① BT: Coin Cell Holders
- ② Appearance For The Product:
M: SMT TYPE
S: 180 TYPE
R: 90 TYPE
- ③ Contact Plating
SN: Tin
GO: Gold Flash
G1: 3U" Gold
G2: 5U" Gold
G3: 10U" Gold
G4: 15U" Gold
G5: 30U" Gold
- ④ Packing Method
A: Tray Packing
R: Tape & Reel Packing
- ⑤ Product Number
CR1220A

Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW ZLA DATE 21/07/2022
 CHECK BobYang DATE 21/07/2022



Atkconn® ATKCONN ELECTRONICS CO., LTD
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: Coin Cell Holders For CR1220
 DRAWING NO: BT-M-GO-R-CR1220A
 PRODUCT NO: BT-M-GO-R-CR1220A

REV	DESCRIPTION	DATE
1		
2		